

# IVAT COATINGS ACADEMY

STUDIO SVILUPPO RICERCA PER L'INDUSTRIA  
REFINISH AUTO YACHTING CARROZZERIA INDUSTRIALE

RESEARCH DEVELOPMENT PERFORMANCE  
FOR INDUSTRY AUTOMOTIVE YACHTING TRUCK

UNI EN ISO 9001:2000



SISTEMA DI GESTIONE  
QUALITÀ CERTIFICATO

CERTIQUALITY  
È MEMBRO DELLA  
FEDERAZIONE CISO



Marchio che identifica  
i prodotti IVAT VOC compatibili

Seal that identifies the IVAT's Voc  
compliant products.

IVAT ACADEMY è anche  
formazione professionale.  
Dei grandi prodotti hanno  
bisogno di essere applicati  
bene e per questo  
mettiamo a disposizione  
dei corsi pratici per  
addestrare il Vostro  
personale alla perfetta  
verniciatura.

IVAT ACADEMY is also  
professional training.  
All best products  
need to be applied well  
and that is the reason why  
we provide practical  
courses to train your staff  
painting perfectly.

**IVAT**  
Coatings

**JACKAL**<sup>®</sup>  
COATINGS

**HIGH  
PERFORMANCE**

*Long Life  
Coatings*

**LOW.V.O.C.**





# HIGH PERFORMANCE

# JACKAL<sup>®</sup> COATINGS

Long Life  
Coatings

LOW.V.O.C.

## SPECIAL PRODUCTS



### KJL.4445

VOC (g/Lt)IIB(e)(840)480 prodotto pronto all'uso Dir 2004/42/CE:

Smalto acrilico lucido realizzato con l'ausilio di nanotecnologie adatto alla verniciatura di camion e qualsiasi altro supporto dove necessita grade adesione, protezione, resistenza superficiale al graffio, agli oli. Si usa direttamente su supporti in acciai, lamiera zincata, alluminio e plastica dura.

Acrylic glossy enamel realized with nanotechnology, good for painting truck-chassis and any other surfaces which needs a great adhesion, protection, superficial anti-scratch and oilresistance. To use directly on steel galvanized sheet, aluminium and hard plastic

	10 - 25 °C	25 - 35 °C	In Vd. ByVd.	In Peso ByWeight	Vol. x Ates By Vd. for Airtes
PRODOTTI / PRODUCT	KJL.4445	KJL.4445	3	100	3
CATALIZZATORE / HARDNER	FK9.5555	FK9.5554	1	33	1
DILUENTE / THINNER			0,2 - 0,4	5 -10	0,1

### KJL.4444

VOC (g/Lt)IIB(i)(840)460 prodotto pronto all'uso Dir. 2004/42/CE

Smalto acrilico semilucido 60 gloss contenente speciali additivi in teflon adatto alla verniciatura di telai di camion e qualsiasi altro supporto dove necessita grade adesione, protezione, resistenza superficiale al graffio, agli oli. Si usa direttamente su supporti in acciai, lamiera zincata, alluminio e plastiche dure.

Semi-glossy acrylic enamel 60 gloss with teflon additive, recommended for painting truck-chassis and any other surface which needs a great adhesion, protection, superficial anti-scratch and oilresistance. To use directly on steel surfaces, galvanized sheets, aluminium and hard plastic

	10 - 25 °C	25 - 35 °C	In Vd. ByVd.	In Peso ByWeight	Vol. x Ates By Vd. for Airtes
PRODOTTI / PRODUCT	KJL.4444	KJL.4444	5	100	5
CATALIZZATORE / HARDNER	FK9.5555	FK9.5554	1	20	1
DILUENTE / THINNER			0,2 - 0,4	5 -10	0,1

### KJL.0333

VOC (g/Lt)IIB(d)(420)420 prodotto pronto all'uso Di 2004/42/CE

Smalto Poliacrilico, brillante, molto coprente rapido nell'indurimento, resistente all'ingiallimento, ottima resistenza meccanica e chimica. Realizzabile miscelando nei rapporti indicati le paste con il coarctore.

Polyacrylic, glossy enamel, very covering, quick hardening, yellowing resistant. Obtainable by mixing pigments and binder in the right mixing ratio

	10 - 25 °C	25 - 35 °C	In Vd. ByVd.	In Peso ByWeight	Vol. x Ates By Vd. for Airtes
PRODOTTI / PRODUCT	KJL.0333	KJL.0333	3	100	3
CATALIZZATORE / HARDNER	FK9.5555	FK9.5554	1	33	1
DILUENTE / THINNER	RDL.S777	RDL.L666	0,2 - 0,4	5 - 10	0,1